

# SPECIFICATION

## AUTOMATIC BATTERY CHARGER MODEL PT-22

ใช้ชาร์จแบตเตอรี่ได้ทั้งแบบน้ำและแบบแห้ง

CONTROL SYSTEM	SWITCHING DC POWER SUPPLY / TIMER CONTROL	
CHARGER SYSTEM	CONSTANT VOLTAGE AND LIMIT CURRENT	
COOLING SYSTEM	BLOWER	
INPUT VOLTAGE	220V AC -20%+15%(176-253VAC)	
INPUT FREQUENCY	50Hz	
INPUT PROTECTION	FUSE OR BREAKER	
OUTPUT CHARGER	BATTERY 12VDC	BATTERY 24VDC
FLOAT CHARGE	13.5-13.8 V	27-27.6 V
EQUALIZING CHARGER	14.2-14.6 V	28.4-29.2 V
OUTPUT VOLTAGE REGULATOR	+/- 1%	
OUTPUT CHARGE 12V CURRENT	ADJUST 18-40ADC (SELECT CURRENT 50%) ADJUST 36-80ADC (SELECT CURRENT 100%)	
OUTPUT CHARGE 24V CURRENT	ADJUST 15-35ADC (SELECT CURRENT 50%) ADJUST 30-70ADC (SELECT CURRENT 100%)	
RATING	100% CONTINUOUS	
TEMPERATURE	45 °C	
EFFICIENCY	MORE THAN 90% AT FULL LOAD	
OUTPUT PROTECTION	OUTPUT LIMIT CURRENT AND FUSE	
INDICATOR LED LAMP	INPUT, OUTPUT, EQUAL CH, FLOAT CH, STAND BY CH, OUTPUT FUSE OUTPUT DIGITAL VOLT-AMP METER	
CABLE INPUT / OUTPUT	CABLE PLUG AC. AND CABLE CRIP FOR BATTERY	
DIMENSION ( W x D x H )Cm.	34 x 27 x 28.5 Cm. FOR PT-22	
WEIGHT	14.5 Kg	