

SPECIFICATION

BATTERY CHARGER INPUT 380V 3PHASE OUTPUT 340V RATING 0-50ADC 8 CHANNEL

POWER SECTION

VOLTAGE INPUT	380 VAC 3 PHASE 46-55 Hz
VARIABLE INPUT VOLTAGE RANGE	350-415 Vac
INPUT CURRENT	250 A AT FULL LOAD
NUMBER OF CHANNEL	8
VOLTAGE OUTPUT	340 VDC (340 VDC x 8 CHANNELS)
OUTPUT CURRENT	0-50 ADC (0-50A x 8 CHANNELS)
TRANSFORMER	ISOLATED DRY TYPE
RECTIFIER	FULL BRIDGE SCR PHASE CONTROL
COOLING SYSTEM	BLOWER

CONTROL AND PROTECTION SECTION

MAIN DISPLAY	TFT LCD TOUCH SCREEN 320 x 240 Pixels 5.7" 256 Color VIRTUAL TOUCH KEYPAD
LAMP & LED	LAMP PHASE R, S, T INPUT LED INPUT, OPERATE, OVERHEAT, ALARM
PROTECTION	MAIN CIRCUIT BREAKER SUB CIRCUIT BREAKER FUSE OUTPUT, CONTROL CIRCUIT
ACCESSORIES	BIDING POST SIGNAL VOLT, AMP