

AUTOMATIC STANDBY BATTERY CHARGER : BC-03

เครื่องชาร์จแบตเตอรี่อัตโนมัติ ที่เหมาะสำหรับงานประเภทไฟฉุกเฉิน เจนเนอเรเตอร์
สแตนบายชาร์จได้ สามารถต่อชาร์จกับแบตเตอรี่ไว้ได้ตลอด 24 ชั่วโมง

คุณสมบัติของเครื่องชาร์จแบตเตอรี่ BC-03

เป็นทั้งเครื่องชาร์จแบตเตอรี่แบบอัตโนมัติและเป็นแหล่งจ่ายไฟดีซี. ระบบ SWITCHING POWER SUPPLY / TIMER CONTROL มีความเที่ยงตรงและประสิทธิภาพสูง มีรีเลย์และการสูญเสียที่ต่ำมาก
ประโยชน์ของเครื่องชาร์จแบตเตอรี่ BC-03

- ใช้ชาร์จแบตเตอรี่ทั้งแบบแห้งและแบบแฉ่ำ
- FOR STARTING BATTERY
- SEALED LEAD ACID BATTERY
- DEEP CYCLE BATTERY (แบตเตอรี่น้ำ)

BC-03



รับประกัน 1 ปี

SPECIFICATION

Control System	Switching Dc Power Supply / Timer Control	Switching Dc Power Supply / Timer Control
Charger System	Constant Voltage And Limit Current	Constant Voltage And Limit Current
Cooling System	Self Air	Self Air
Input Voltage	220v Ac -20%+15%(176-253vac)	220v Ac -20%+15%(176-253vac)
Input Current	0.4 Aac	0.4 Aac
Input Frequency	50hz	50hz
Input Protection	Fuse	Fuse
Output Charger	Battery 12vdc	Battery 24vdc
Float Charge	13.5-13.8 V	27-27.6 V
Equalizing Charger	14.2-14.6 V (Automatic Switch To Float Charge)	28.4-29.2 V (Automatic Switch To Float Charge)
Output Voltage Regulator	+/- 1.5%	+/- 1.5%
Output Charge	5 Adc	3 Adc
Rating	100% Continuous	100% Continuous
Temperature	45 °C	45 °C
Efficiency	More Than 90% At Full Load	More Than 90% At Full Load
Output Protection	Output Limit Current And Fuse	Output Limit Current And Fuse
Indicator Led Lamp	Reverse, Equal Ch, Float Ch, Output Fuse	Reverse, Equal Ch, Float Ch, Output Fuse
Meter	Output Amp Meter	Output Amp Meter
Safety Battery	Reverse Polarity Protection	Reverse Polarity Protection
Cable Input / Output	Cable Plug Ac. And Cable Crip For Battery	Cable Plug Ac. And Cable Crip For Battery
Dimension (W X D X H)Cm.	14 X 20 X 16 Cm.	14 X 20 X 16 Cm.
Weight	2.55 Kg	2.50 Kg